

t r a c k s i d e

## 2-PAIR COPPER TERMINATION BOX



The Cannon 2-Pair Copper Termination Box measures externally 234mm high x 135mm wide x 69mm deep. It is bolted to a square section galvanised 3mm thick steel post which is barbed at its lower end to resist withdrawal from the ground. The box is inclined at an ergonomic 15° to the vertical, making internal cabling access easier. The post to which the box is fixed is 1200mm long. The lid is secured with a padlock (not supplied).

Two versions are available: C096800B and C096800C, which vary with respect to the cable entry gland hole provision and in the resultant pre-configuration of component mountings within the box.

C096800B has three cable entry holes in a row: 2 x Ø26mm + 1 x Ø17mm. C096800C has four staggered cable entry holes Ø20mm.

**Please contact the  
Sales Team for further  
information on:  
+44(0)1425 638148 or  
sales@cannontech.co.uk**



t r a c k s i d e

## PRODUCT FEATURES

- IIP45 rating
- Single fully removable sliding cover
- Internal fitments to customers' requirements
- Fully welded construction
- Cover secured with padlock available
- Manufactured from Stainless Steel Type 304
- Supplied complete with post
- Includes pre-fitted DIN rail and earth point
- Used in Rail side applications for 2-pair copper termination and cable jointing



**Cannon Technologies Ltd**  
**Queensway, New Milton,**  
**Hampshire. BH25 5NU. UK**  
**Tel: +44(0)1425 638148**  
**Email: [sales@cannontech.co.uk](mailto:sales@cannontech.co.uk)**  
**[www.cannontech.co.uk](http://www.cannontech.co.uk)**

